
**RECOMMENDED
CONDITIONS OF APPROVAL AND
STANDARD DEVELOPMENT REQUIREMENTS
May 15, 2024**

Planning Application **2022-7340**
1689 S. Wolfe Road

SPECIAL DEVELOPMENT PERMIT to demolish an existing one-story commercial building and construct a new 1,000 square foot one-story office building and 4,967 square foot two-story office building with podium parking. The project requests a deviation to allow 20-foot front yard setback, where 70 feet minimum is required.

The following Conditions of Approval [COA] and Standard Development Requirements [SDR] apply to the project referenced above. The COAs are specific conditions applicable to the proposed project. The SDRs are items which are codified or adopted by resolution and have been included for ease of reference, they may not be appealed or changed. The COAs and SDRs are grouped under specific headings that relate to the timing of required compliance. Additional language within a condition may further define the timing of required compliance.

In addition to complying with all applicable City, County, State and Federal Statutes, Codes, Ordinances, Resolutions and Regulations, Permittee expressly accepts and agrees to comply with the following Conditions of Approval and Standard Development Requirements of this Permit:

GC: THE FOLLOWING GENERAL CONDITIONS AND STANDARD DEVELOPMENT REQUIREMENTS SHALL APPLY TO THE APPROVED PROJECT.

GC-1. CONFORMANCE WITH APPROVED PLANNING APPLICATION:
All building permit drawings and subsequent construction and operation shall substantially conform with the approved planning application, including: drawings/plans, materials samples, building colors, and other items submitted as part of the approved application. Any proposed amendments to the approved plans or Conditions of Approval are subject to review and approval by the City. The Director of Community Development shall determine whether revisions are considered major or minor. Minor changes are subject to review and approval by the Director of Community Development. Major changes are subject to review at a public hearing. [COA] [PLANNING]

GC-2. ENTITLEMENTS—EXERCISE AND EXPIRATION:

The approved entitlements shall be null and void two years from the date of approval by the final review authority if the approval is not exercised, unless a written request for an extension is received prior to the expiration date and is approved by the Director of Community Development. [SDR] (PLANNING)

GC-3. ENTITLEMENTS—DISCONTINUANCE AND EXPIRATION:

The entitlements shall expire if discontinued for a period of one year or more. [SDR] (PLANNING)

GC-4. INDEMNITY:

The applicant/developer shall defend, indemnify, and hold harmless the City, or any of its boards, commissions, agents, officers, and employees (collectively, "City") from any claim, action, or proceeding against the City to attack, set aside, void, or annul, the approval of the project when such claim, action, or proceeding is brought within the time period provided for in applicable state and/or local statutes. The City shall promptly notify the developer of any such claim, action or proceeding. The City shall have the option of coordinating the defense. Nothing contained in this condition shall prohibit the City from participating in a defense of any claim, action, or proceeding if the City bears its own attorney's fees and costs, and the City defends the action in good faith. [COA] [OFFICE OF THE CITY ATTORNEY]

GC-5. NOTICE OF FEES PROTEST:

As required by California Government Code Section 66020, the project applicant is hereby notified that the 90-day period has begun as of the date of the approval of this application, in which the applicant may protest any fees, dedications, reservations, or other exactions imposed by the city as part of the approval or as a condition of approval of this development. The fees, dedications, reservations, or other exactions are described in the approved plans, conditions of approval, and/or adopted city impact fee schedule. [SDR] [PLANNING / OCA]

GC-6. PUBLIC IMPROVEMENTS:

Developer shall install public improvements as required by the City, including but not limited to, curb & gutter, sidewalks, driveway approaches, street pavements, utility connections, meters/vaults, trees and landscaping, signage, striping, etc.

All public improvements shall be designed and constructed in accordance with current City design standards, standard details and specifications, and Americans with Disabilities Act (ADA) requirements where applicable, unless otherwise approved by the Department of Public Works. The site development plan with sheets C2.0 to C5 dated 12/01/2023 is subject to change during the plan check process.

The developer is required to complete the installation of all public improvements and other improvements deemed necessary by the Public Works Department, prior to occupancy of the first building, or to the satisfaction of the Public Works Department. [COA] [PUBLIC WORKS]

GC-7. OFF-SITE IMPROVEMENT PLANS:

Submit off-site improvement plans separate from the Building on-site improvement plans as the off-site improvement plans are approved through a Public Works Encroachment Permit process. Sheets C2.0 to C5 dated 12/01/2023 are subject to change during the plan check process. [SDR] [PUBLIC WORKS]

GC-8. ENCROACHMENT PERMIT:

Prior to any work in the public right-of-way, obtain an encroachment permit with insurance requirements for all public improvements including a traffic control plan per the latest California Manual on Uniform Traffic Control Devices (MUTCD) standards to be reviewed and approved by the Department of Public Works. [COA] [PUBLIC WORKS]

GC-9. STORMWATER MANAGEMENT PLAN:

Project is subject to Provision C3, of the Municipal Regional Stormwater Permit Order No. R2-2022-0018, as determined by a completed Stormwater Management Plan Data Form, and therefore must submit a Stormwater Management Plan as per SMC 12.60.210 prior to issuance of the building permit. [SDR] [PLANNING]

PS: THE FOLLOWING CONDITIONS SHALL BE MET PRIOR TO SUBMITTAL OF ENCROACHMENT PERMIT, BUILDING PERMIT AND/OR GRADING PERMIT.

PS-1. SANITARY SEWER ANALYSIS:

Prior to first off-site plan check submittal, submit a focused sanitary sewer analysis, to be reviewed and approved by the City, identifying the overall project impact to the City's existing sanitary sewer main(s). This includes, but is not limited to, the following:

- a) A detailed estimate of water consumption in gallons per day or estimate of sanitary sewer discharge in gallons per day; and
- b) Any incremental impact that will result from the new project in comparison to the existing sewer capacity of the immediate downstream mainline as needed, and allocation of wastewater discharge from the project site to each of the proposed laterals. Any deficiencies in the existing system in the immediate vicinity of the project will need to be addressed and resolved at the expense of the developer as part of the off-site improvement plans. Sewer flow data may be required as needed. Any mitigation

improvements needed shall be incorporated into the first plan check submittal. [COA] [PUBLIC WORKS]

BP: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS SUBMITTED FOR ANY DEMOLITION PERMIT, BUILDING PERMIT OR GRADING PERMIT AND SHALL BE MET PRIOR TO THE ISSUANCE OF SAID PERMIT(S).

BP-1. CONDITIONS OF APPROVAL:

Final plans shall include all Conditions of Approval included as part of the approved application starting on sheet 2 of the plans. [COA] [PLANNING]

BP-2. RESPONSE TO CONDITIONS OF APPROVAL:

A written response indicating how each condition has or will be addressed shall accompany the building permit set of plans. [COA] [PLANNING]

BP-3. NOTICE OF CONDITIONS OF APPROVAL:

A Notice of Conditions of Approval shall be filed in the official records of the County of Santa Clara and provide proof of such recordation to the City prior to issuance of any City permit, allowed use of the property, or Final Map, as applicable. The Notice of Conditions of Approval shall be prepared by the Planning Division and shall include a description of the subject property, the Planning Application number, attached conditions of approval and any accompanying subdivision or parcel map, including book and page and recorded document number, if any, and be signed and notarized by each property owner of record.

For purposes of determining the record owner of the property, the applicant shall provide the City with evidence in the form of a report from a title insurance company indicating that the record owner(s) are the person(s) who have signed the Notice of Conditions of Approval. [COA] [PLANNING]

BP-4. BLUEPRINT FOR A CLEAN BAY:

The building permit plans shall include a "Blueprint for a Clean Bay" on one full sized sheet of the plans. [SDR] [PLANNING]

BP-5. ROOF EQUIPMENT:

Roof vents, pipes and flues shall be combined and/or collected together on slopes of roof or behind parapets out of public view as per Title 19 of the Sunnyvale Municipal Code and shall be painted to match the roof. [COA] [PLANNING]

BP-6. DEMOLITION/CONSTRUCTION/RECYCLING WASTE REPORT FORM:

To mitigate the impacts of large projects on local waste disposal, recycling levels and the migration of PCBs, demolition waste weights/volumes including hazardous waste manifests for applicable structures with PCB concentrations greater than 50 ppm, construction weights/volumes, and recycling weights/volumes are to be reported to the City using Sunnyvale.wastetracking.com hosted by Green Halo. As part of the project's construction specifications, the developer shall track the type, quantity, and disposition of materials generated, and submit these records through the website both periodically and at project completion. [COA] [ENVIRONMENTAL SERVICES]

BP-7. SOLID WASTE DISPOSAL AND RECYCLING DESIGN PLAN:

A detailed solid waste disposal and recycling design plan shall be submitted for review and approval by the Director of Community Development prior to issuance of building permit. The solid waste disposal plan and building permit plans shall demonstrate compliance with current City requirements and guidelines for non-residential projects. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

BP-8. SOLID WASTE RECEPTACLES AND ENCLOSURES:

All exterior recycling and solid waste shall be confined to approved receptacles and enclosures. [COA] [ENVIRONMENTAL SERVICES]

BP-9. SOLID WASTE AND RECYCLING ENCLOSURE:

The building permit plans shall include details for the installation of recycling and solid waste enclosures that are consistent with SMC 19.38.030. The solid waste disposal and recycling facilities within the enclosure area or within buildings shall be designed with adequate size, space and clearance based upon City's latest guidelines. The required enclosures shall:

- a) Match the design, materials and color of the main building;
- b) Be of masonry construction;
- c) Be screened from view;
- d) All gates, lids and doors shall be closed at all times;
- e) Shall not conflict with delivery/receiving areas;
- f) Shall be consistent with the approved Solid Waste and Recycling Management Plan;
- g) Solid waste and recycling diversion systems shall be incorporated into the facilities and tenant improvements. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

BP-10. SOLID WASTE SERVICES:

The Property Manager is responsible for moving carts from the trash enclosure to the curb along Martin Ave on service days. Failure to do so

will result in no service for the garbage and recycling containers on site.
[COA] [ENVIRONMENTAL SERVICES]

BP-11. STORMWATER MANAGEMENT PLAN:

Submit two copies of a Stormwater Management Plan subject to review and approval by Director of Community Development, pursuant to SMC 12.60, prior to issuance of building permit. The Stormwater Management Plan shall include an updated Stormwater Management Data Form. Sheets C2.0 to C5 dated 12/01/2023 and other appropriate sheets are subject to change during the plan check process. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

BP-12. STORMWATER MANAGEMENT PLAN THIRD-PARTY CERTIFICATION:

Third-party certification of the Stormwater Management Plan is required per the following guidance: City of Sunnyvale – Stormwater Quality BMP Applicant Guidance Manual for New and Redevelopment Projects - Addendum: Section 3.1.2 Certification of Design Criteria Third-Party Certification of Stormwater Management Plan Requirements. The third-party certification shall be provided prior to building permit issuance. [SDR] [PLANNING/ENVIRONMENTAL SERVICES]

BP-13. BEST MANAGEMENT PRACTICES - STORMWATER:

The project shall comply with the following source control measures as outlined in the BMP Guidance Manual and SMC 12.60.230. Best management practices shall be identified on the building permit set of plans and shall be subject to review and approval by the Director of Public Works:

- a) Storm drain stenciling. The stencil is available from the City's Environmental Services Department, which may be reached by calling (408) 730-773-7717.
- b) Landscaping that minimizes irrigation and runoff, promotes surface infiltration where possible, minimizes the use of pesticides and fertilizers, and incorporates appropriate sustainable landscaping practices and programs such as Bay-Friendly Landscaping.
- c) Appropriate covers, drains, and storage precautions for outdoor material storage areas, loading docks, repair/maintenance bays, and fueling areas.
- d) Covered trash, food waste, and compactor enclosures.
- e) Plumbing of the following discharges to the sanitary sewer, subject to the local sanitary sewer agency's authority and standards:
 - i. Discharges from indoor floor mat/equipment/hood filter wash racks or covered outdoor wash racks for restaurants.
 - ii. Dumpster drips from covered trash and food compactor enclosures.

- iii. Discharges from outdoor covered wash areas for vehicles, equipment, and accessories.
- iv. Swimming pool water, spa/hot tub, water feature and fountain discharges if discharged to onsite vegetated areas is not a feasible option.
- v. Fire sprinkler test water, if discharged to onsite vegetated areas is not a feasible option. [SDR] [PLANNING]

BP-14.TREATMENT OF PUBLIC RIGHT-OF-WAY STORMWATER

Developer has acknowledged per the meeting with City's staffs on 02/14/2024 that stormwater in the public right-of-way area disturbed during construction is required to be treated. The proposed Treatment Control Measure (TCM) shall be located on private property, not in public right-of-way and / or existing easements of any kind. Sheets C2.0 to C5 dated 12/01/2023 and other appropriate sheets are subject to change during the plan check process. [COA] [PUBLIC WORKS/PLANNING/ENVIRONMENTAL SERVICES]

BP-15.BICYCLE PARKING:

Provide at least one (1) bicycle parking spaces (5% of the total number of vehicular parking spaces provided) near the main entrance and/or high visible areas per Sunnyvale Municipal Code Section 19.46.150. Seventy-five percent of required bicycle parking spaces shall be bicycle racks. Clearly indicate the location and number of spaces on building permit plans. [COA] [PUBLIC WORKS]

BP-16.CONSTRUCTION MATERIAL AND STAGING:

All construction related materials, equipment, and construction workers parking need to be managed on-site and not located in any public right-of-ways or public easements. [COA] [PUBLIC WORKS]

BP-17.EXHAUST AND OPENINGS:

No exhaust fans, doors, windows, or openings, of any kind shall be placed on the wall or where residential use abuts the proposed building, except as may be required by the City, nor shall any machines or fans be placed on the roof of the building which exhaust dust or odors. The building permit plans shall clearly indicate the location of all exhaust equipment, doors and window and shall be subject to review and approval by the Community Development Director. [COA] [PLANNING]

BP-18.LANDSCAPE PLAN:

Landscape and irrigation plans shall be prepared by a certified professional, and shall comply with Sunnyvale Municipal Code Chapter 19.37 requirements. Landscape and irrigation plans are subject to review and approval by the Director of Community Development through

the submittal of a Miscellaneous Plan Permit (MPP). The landscape plan shall include the following elements:

- a) Provide screening trees along the north property line adjacent to the residential property.
- b) All areas not required for parking, driveways or structures shall be landscaped.
- c) Provide trees at minimum 30 feet intervals along side and rear property lines, except where mature trees are located immediately adjoining on neighboring property.
- d) Provide deciduous trees along north side of the building for passive solar heating purposes.
- e) Ten percent (10%) of the trees shall be 24-inch box size or larger and no tree shall be less than 15-gallon size.
- f) Provide a ten-foot-wide landscape buffer along the north property line adjacent to the residential property and along the east property line adjacent to the City property.
- g) Ground cover shall be planted so as to ensure full coverage eighteen months after installation. [COA] [PLANNING]

BP-19.LANDSCAPE MAINTENANCE PLAN:

Prepare a landscape maintenance plan subject to review and approval by the Director of Community Development prior to issuance of building permit. [COA] [PLANNING]

BP-20.LANDSCAPE BUFFER:

Maintain the existing seven and one-half feet fence (five and one-half feet masonry wall with two feet wood mesh) along the north side of the property line adjoining the single-family home. Should this fence be replaced, install a new masonry wall at equal height measured from the highest adjoining grade, of a design subject to review by the Director of Community Development. [SDR] [PLANNING]

BP-21.EXTERIOR LIGHTING PLAN:

Prior to issuance of a Building Permit submit an exterior lighting plan, including fixture and pole designs, for review and approval by the Director of Community Development. Driveway and parking area lights shall include the following:

- a) Sodium vapor (or illumination with an equivalent energy savings).
- b) Pole heights to be uniform and compatible with the areas, including the adjacent residential areas. Light standards shall not exceed 18 feet on the interior of the project and 8 feet in height on the periphery of the project near residential uses.
- c) Provide photocells for on/off control of all security and area lights.
- d) All exterior security lights shall be equipped with vandal resistant covers.

- e) Wall packs shall not extend above the roof of the building.
- f) Lights shall have shields to prevent glare onto adjacent properties.
[COA] [PLANNING]

BP-22.PHOTOMETRIC PLAN:

Prior to issuance of a Building Permit submit a contour photometric plan for approval by the Director of Community Development. The plan shall meet the specifications noted in the Standard Development Requirements. [COA] [PLANNING]

BP-23.LIGHTING POLE HEIGHTS:

Pole heights shall not to exceed 16 feet in height feet unless approved by the Director of Community Development. [COA] [PLANNING]

BP-24.LIGHTING SPACING:

Installation of lights at a minimum of 50 feet intervals along all private streets. [COA] [PLANNING]

BP-25.PARKING LOT STRIPING:

Parking spaces should be marked in the following manner to encourage careful parking and increase usability of spaces.

- a) Double lines, one foot apart (as measured from the center) and four inches wide should mark the sides of each space.
- b) Lines should be 16 feet long, with a rounded radius end. [COA] [PLANNING]

BP-26.GREEN BUILDING:

The plans submitted for building permits shall demonstrate the project achieves a minimum of 80 points on the Green Point Rated checklist, or the minimum points required effective at the time of building permit submittal. The project plans shall be accompanied with a letter from the project's Green Point Rater/LEED AP verifying the project is designed to achieve the required points. [COA] [PLANNING] [BUILDING]

BP-27.CONSTRUCTION MANAGEMENT PLAN:

The project applicant shall implement a Construction Management Plan (CMP) to minimize impacts of construction on surrounding residential uses to the extent possible. The CMP shall be subject to review and approval by the Director of Community Development and Director of Public Works with a separate Miscellaneous Plan Permit (MPP) prior to issuance of a demolition permit, grading permit, or building permit. The CMP shall identify measures to minimize the impacts of construction including the following:

- a) Measures to control noise by limiting construction hours to those allowed by the SMC, avoiding sensitive early morning and evening hours, notifying residents prior to major construction activities, and appropriately scheduling use of noise-generating equipment.
- b) Use 'quiet' models of air compressors and other stationary noise sources where such technology exists.
- c) Equip all internal combustion engine-driven equipment with mufflers, which are in good condition and appropriate for the equipment.
- d) Locate all stationary noise-generating equipment, such as air compressors and portable power generators, as far away as possible from residences or other noise-sensitive land uses.
- e) Locate staging areas and construction material areas as far away as possible from residences or noise-sensitive land uses.
- f) Route all construction traffic to and from the project site via designated truck routes where possible. Prohibit construction-related heavy truck traffic in residential areas where feasible. Obtain approval of proposed construction vehicle truck routes from the Department of Public Works.
- g) Manage construction parking so that neighbors are not impacted by construction vehicles. When the site permits, all construction parking shall be on-site and not on the public streets.
- h) Prohibit unnecessary idling of internal combustion engine-driven equipment and vehicles.
- i) Notify all adjacent business, residents, and noise-sensitive land uses of the construction schedule in writing. Notify nearby residences of significant upcoming construction activities at appropriate stages in the project using mailing or door hangers.
- j) Designate a "disturbance coordinator" who would be responsible for responding to any local complaints about construction noise. The disturbance coordinator will determine the cause of the noise complaint and will require that reasonable measures warranted to correct the problem be implemented. Conspicuously post a telephone number for the disturbance coordinator at the construction site and include it in the notice sent to neighbors regarding the construction schedule. [COA] [PLANNING] [PUBLIC WORKS]

BP-28. CONSTRUCTION AIR QUALITY MITIGATION MEASURES:

Prior to the issuance of grading or building permits, the Bay Area Air Quality Management District's (BAAQMD) basic construction mitigation measures from Table 8-1 of the BAAQMD 2011 CEQA Air Quality Guidelines (or subsequent updates) shall be noted on the construction documents, including the following:

- a) All exposed surfaces (e.g., parking areas, staging areas, soil piles, graded areas, and unpaved access roads) shall be watered two times per day.
- b) All haul trucks transporting soil, sand, or other loose material off-site shall be covered.
- c) All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day. The use of dry power sweeping is prohibited.
- d) All vehicle speeds on unpaved roads shall be limited to 15 miles per hour (mph).
- e) All roadways, driveways, and sidewalks to be paved shall be completed as soon as possible. Building pads shall be laid as soon as possible after grading unless seeding or soil binders are used.
- f) All construction equipment shall be maintained and properly tuned in accordance with manufacturers' specifications. All equipment shall be checked by a certified mechanic and determined to be running in proper condition prior to operation.
- g) A publicly visible sign shall be posted with the telephone number and person to contact at the lead agency regarding dust complaints. This person shall respond and take corrective action within 48 hours. The BAAQMD's phone number shall also be visible to ensure compliance with applicable regulations. [COA]
[PLANNING]

BP-29.CONSTRUCTION NOISE MITIGATION MEASURES:

The project shall employ site-specific noise attenuation measures during construction to reduce the generation of construction noise and vibration. These measures shall be included in a noise control plan that shall be submitted for review and approval by the Director of Community Development. Measures specified in the noise control plan and implemented during construction shall include, at a minimum, the following noise control strategies:

- a) Equipment and trucks used for construction shall use the best available noise control techniques (e.g., improved mufflers, equipment redesign, use of intake silencers, ducts, engine enclosures, and acoustically attenuating shields or shrouds);
- b) Impact tools (e.g., jackhammers, pavement breakers, and rock drills) used for construction shall be hydraulically or electrically powered wherever possible to avoid noise associated with compressed air exhaust from pneumatically powered tools; and
- c) Stationary noise sources shall be located as far from adjacent receptors as possible, and they shall be muffled and enclosed within temporary sheds, incorporate insulation barriers, or include other measures.

- d) Pile-driving is prohibited unless authorized by the Director of Community Development. If authorized, noise and vibration reducing pile-driving techniques shall be employed during construction and will be monitored to ensure no damage to nearby structures occurs (i.e., vibrations above peak particle velocity (PPVs) of 0.25 inches per second at nearby structures). These techniques shall include:
- i) Installing intake and exhaust mufflers on pile-driving equipment;
 - ii) Vibrating piles into place when feasible, and installing shrouds around the pile-driving hammer where feasible as determined by the Director of Community Development;
 - iii) Implementing “quiet” pile-driving technology (such as pre-drilling of piles and the use of more than one pile driver to shorten the total pile driving duration), where feasible, in consideration of geotechnical and structural requirements and conditions;
 - iv) Using cushion blocks to dampen impact noise, if feasible based on soil conditions as determined by the Director of Community Development. Cushion blocks are blocks of material that are used with impact hammer pile drivers. They consist of blocks of material placed atop a piling during installation to minimize noise generated when driving the pile. Materials typically used for cushion blocks include wood, nylon and micarta (a composite material); and
 - v) At least 48 hours prior to pile-driving activities, notifying building owners and occupants within 600 feet of the project area of the dates, hours, and expected duration of such activities. [COA][PLANNING]

BP-30. PARKING MANAGEMENT PLAN (NONRESIDENTIAL):

A Parking Management Plan shall be submitted for review and approval by the Director of Community Development prior to issuance of a building permit. The Parking Management Plan shall include the following:

- a) Employees shall be required to park on the site.
- b) Indicate how parking will be shared between different tenants in the two buildings. Specify the location and term of short-term parking for each tenants.
- c) Specify the location of the required carpool/car share spaces.
- d) Provide adequate signage to direct traffic and pedestrians. [COA][PLANNING]

EP: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED AS PART OF AN ENCROACHMENT PERMIT APPLICATION.

EP-1. COMPLETE OFF-SITE IMPROVEMENT PLAN SET:

a complete plan check set applicable to the project, which may include street improvement plans, streetscape plans, signing/stripping plans, erosion control plans, and traffic control plans shall be submitted as part of the first off-site improvement plans, including on-site and off-site engineering cost estimate and the initial Engineer and Inspection plan review fee. Joint trench plans may be submitted at a later date. No partial sets are allowed unless otherwise approved by the Department of Public Works. Sheets C2.0 to C5 dated 12/01/2023 are subject to change during plan check process. See Improvement Plan Checklist and Improvement Plan Submittal Checklist at the following 2 links:

<https://www.sunnyvale.ca.gov/home/showpublisheddocument/1656/638097347304330000>

[https://www.sunnyvale.ca.gov/home/showpublisheddocument/1654/637820856582800000\[coa\] \[pUBLIC WORKS\]](https://www.sunnyvale.ca.gov/home/showpublisheddocument/1654/637820856582800000[coa] [pUBLIC WORKS])

EP-2. UPGRADE OF EXISTING PUBLIC IMPROVEMENTS:

As part of the off-site improvement plan review and approval, any existing public improvements to be re-used by the project, which are not in accordance with current City standards and are not specifically identified in the herein project conditions shall be upgraded to current City standards and as required by the Department of Public Works. [COA] [PUBLIC WORKS]

EP-3. BENCHMARKS:

The improvement plans shall be prepared by using City's latest benchmarks (NAVD88) available on City's website <https://www.sunnyvale.ca.gov/home/showpublisheddocument/1590/637820851886430000>

Plans based on NGVD29 will not be accepted. [COA] [PUBLIC WORKS]

EP-4. UTILITY CONNECTION:

This project requires connection to all City utilities or private utilities operating under a City or State franchise which provide adequate levels of service. [COA] [PUBLIC WORKS]

EP-5. UTILITY CONNECTION TO THE MAIN:

The proposed sanitary sewer lateral connecting to the existing main line shall be WYE connection. [SDR] [PUBLIC WORKS]

EP-6. POTHOLING OF EXISTING UTILITIES:

Concurrent with the initial submittal of off-site improvement plans, obtain an encroachment permit for potholing purposes to locate existing utilities. Use pothole information to identify possible conflict between

the proposed location of City trees and existing utilities, proposed joint trench, and proposed connection of gravity utilities. Potholing is to take place in a timely manner so that this does not hold up the review of the improvement plans. [COA] [PUBLIC WORKS]

EP-7. EXISTING UTILITY ABANDONMENT/RELOCATION:

Developer is responsible for research on all existing utility lines to ensure that there are no conflicts with the project. All existing utility lines (public or private) and/or their appurtenances not serving the project and/or have conflicts with the project, shall be capped, abandoned, removed, relocated and/or disposed of to the satisfaction of the City. Existing public facilities within the street right-of-way shall be abandoned per City's Abandonment Notes and procedures, including abandonment by other utility owners. [COA] [PUBLIC WORKS]

EP-8. MODIFICATIONS TO EXISTING PUBLIC UTILITIES:

Developer is required to pay for all changes or modifications to existing City utilities, streets and other public utilities within or adjacent to the project site, including but not limited to utility facilities/conduits/vaults relocation due to grade change in the sidewalk area, caused by the development. [COA] [PUBLIC WORKS]

EP-9. DRY UTILITIES:

Submit dry utility plans and/or joint trench plans (PG&E, telephone, cable TV, fiber optic, etc.) to the Public Works Department for review and approval prior to issuance of any permits for utility work within any public right-of-way or public utility easements. Separate encroachment permits shall be required for various dry utility construction. [SDR] [PUBLIC WORKS]

EP-10. WET UTILITIES:

All wet utilities (water, sanitary sewer, storm drain) on private property shall be privately owned and maintained. The fire and domestic water systems shall be privately owned and maintained beyond the meter. [COA] [PUBLIC WORKS]

EP-11. RE-USE OF EXISTING CITY UTILITY SERVICE LINES:

The re-use of existing City water service lines is not allowed. Re-use of existing City sanitary sewer and storm drain service lines and appurtenances is subject to City's review and approval. Developer's contractor shall expose the existing facilities during construction for City's evaluation or provide video footage of the existing pipe condition. Developer's contractor shall replace any deficient facilities as deemed necessary by Public Works Department. [COA] [PUBLIC WORKS]

EP-12. SEPARATE DOMESTIC/FIRE PROTECTION SERVICE LINE:

Provide separate fire and domestic service lines to each building. Provide separate fire service tap(s) to the street main for on-site fire hydrants. Install reduced pressure backflow prevention devices (RPBP) behind the street right-of-way for the domestic service line and a reduced pressure detector assembly (RPDA) and 5/8" water meter behind the street right-of-way for the fire service line. Backflows must adhere to City's Cross-Connection Program. Backflow inspection permit and tags are required for all backflow devices. [COA] [PUBLIC WORKS/PUBLIC SAFETY-FIRE PREVENTION]

EP-13. PUBLIC FIRE HYDRANTS:

Remove and replace the existing fire hydrant barrel and existing fire hydrant lateral along Martin Avenue with current City standard Clow-Rich 75. Also, install a new fire hydrant along the South Wolfe Road project frontage with current City standard Clow-Rich 75. New fire hydrant laterals and barrels must be located outside of existing and proposed tree driplines, or as determined by Department of Public Works. Hydrants shall be located per City standard detail 2B and 2B-2. Public fire hydrants shall be maintained a minimum of 3 horizontal feet from trees, vines, shrubs, bushes, and other obstacles. [COA] [PUBLIC WORKS/public safety-fire protection]

EP-14. WATER METER:

The proposed buildings shall have one domestic water service connection to the water main with domestic radio-read water meter and reduced pressure backflow prevention devices per current City standards. For water meter sizes three (3) inches or larger, provide meter sizing calculations to Public Works Department for approval of meter size, as part of the off-site improvement plan submittal. If the buildings water demand requires a water meter 3" or larger, a cut-in tee is required per City standard detail 12B and 12B-1. Provide separate fire service taps with separate reduced pressure detector assembly in accordance with current City standards. Install new radio-read water meter(s) for each point of connection to the water main. Install new backflow prevention devices on the discharge side of water service line on private property. Install backflow preventer enclosure where applicable. Sheet C3.0 dated 12/01/2023 is subject to change during plan check process. [SDR] [PUBLIC WORKS]

EP-15. IRRIGATION SERVICE LINE AND BACKFLOW PREVENTORS:

This project requires to install a separate irrigation water service line (separate from the domestic water service line) with a meter per City's detail 4B and backflow prevention device. Thus, the proposed irrigation water lateral shall tee off from the proposed 3-inch water lateral line in

the pavement area. Sheets C3.0 12/01/2023 sheet is subject to change during the plan check process.

Install new reduced pressure backflow prevention devices on the discharge side of irrigation line on private property. Install backflow preventer enclosure where applicable. Backflows must adhere to City's Cross-Connection Program. Backflow inspection permit and tags are required for all backflow devices. [SDR] [PUBLIC WORKS]

EP-16.SANITARY SEWER CLEANOUT:

Install a new sanitary sewer cleanout at the street right-of-way lines for the proposed sanitary sewer lateral to be used for the project. [SDR] [PUBLIC WORKS]

EP-17.SANITARY SEWER VIDEO:

The contractor shall make a video copy of the interior of the new sanitary sewer main installed prior to it is put into service. [COA] [PUBLIC WORKS]

EP-18.SANITARY SEWER AND STORM DRAIN TRIBUTARY PATTERN:

This project is required to follow the existing sanitary sewer and storm drain tributary pattern. Any deviations would require additional analysis and be subject to approval by the Department of Public Works as part of the off-site improvement plan review process. This project shall not cause any negative impact on the drainage pattern for adjacent properties. [COA] [PUBLIC WORKS]

EP-19.CATCH BASIN TRASH CAPTURE DEVICES AND STENCILING:

Pursuant to SMC 12.60.130, install full trash capture devices on the project site, prior to connecting to the City's storm drain collection system. The developer shall be responsible for perpetual maintenance of those trash capture devices. All storm drain inlet facilities located in the public right-of-way shall be stenciled that read "NO DUMPING". Stencils may be borrowed and returned by coordinating with the Environmental Services Department by calling 408-730-7738. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

EP-20.UTILITY METER/VAULT:

No existing or new utility meters or vaults shall be located within the new driveway approach areas. All existing or new utility vaults serving the project site shall be located on-site and not within the public utility easement, if any. [COA] [PUBLIC WORKS]

EP-21.DRIVEWAY APPROACHES:

Remove existing driveway approach and install a new driveway approach per City's detail 6C-2 along the project frontage to comply with Americans with Disabilities Act (ADA) requirements and per city standard details and specifications. The new driveway approach shall maintain full access to the adjacent Gas Station property and comply with the recorded Non-Exclusive Easement for Ingress and Egress. All unused existing driveway approaches shall be replaced with new curb, gutter and sidewalk. [COA] [PUBLIC WORKS]

EP-22. DRIVEWAY VISION TRIANGLE:

Comply with the driveway vision triangle requirements at all driveway approaches on Wolfe Road per SMC 19.34.060. Show location of sidewalk relative to the driveway vision triangle. [COA] [PUBLIC WORKS]

EP-23. STREETScape IMPROVEMENTS:

Along the South Wolfe Road project frontage, remove existing curb, gutter and sidewalk and install a new 1-foot-wide gutter, and 10-foot-wide attached sidewalk with 4'x5' treewell per City's detail 9C-2. Provide sidewalk transition to conform to existing sidewalk at both ends of the project limits, or as approved by the Director of Public Works.

Along the Martin Avenue project side, remove existing curb, gutter and sidewalk and install a new 2-foot-wide gutter and 6-foot-wide detached sidewalk per City's detail 9C-1A. To protect the existing mature trees in park-strip, new sidewalk width behind the existing mature trees shall maintain a minimum 4 feet. Provide sidewalk transition to conform to existing sidewalk at both ends of the project limits, or as approved by the Director of Public Works. Sheets C2.0 to C5 dated 12/01/2023 are subject to change during the plan check process.

Perpetual maintenance of existing sidewalk and new sidewalk improvements along the project frontages shall be the sole responsibility of the property owner. [COA] [PUBLIC WORKS]

EP-24. STREET PAVEMENT:

Along the South Wolfe Road project frontage, grind minimum 2 inches of existing asphalt concrete at minimum 10 feet on both sides of the trenches and overlay with minimum 2 inches of new asphalt concrete at minimum 10 feet on both sides of the trenches, and grind minimum 2 inches of existing asphalt concrete and overlay with minimum 2 inches of new asphalt concrete from the lip of gutter to the first travel lane, unless otherwise approved by the Department of Public Works with alternatives. Sheet C3.0 dated 12/01/2023 is subject to change during plan check process.

Along the Martin Avenue project frontage, apply Type II slurry seal from lip of gutter to lip of gutter, unless otherwise approved by the Department of Public Works with alternatives. [SDR] [PUBLIC WORKS]

EP-25. SIGNING AND STRIPING PLANS:

Submit a signing and striping plan in accordance with the latest edition of the CA MUTCD to City for review and approval by the Public Works Department. [SDR] [PUBLIC WORKS]

EP-26. TRAFFIC CONTROL PLAN:

Submit a traffic control plan with the off-site improvement plans for review and approval. Per the City's Temporary Traffic Control Checklist, the traffic control plan shall include a summary of the traffic control types, dates, times and blocks affected. All construction related materials, equipment, and construction workers parking need to be stored on-site and the public streets need to be kept free and clear of construction debris. [COA] [PUBLIC WORKS]

EP-27. PROTECTION OF EXISTING TREES:

No utility trench shall be allowed within 15' radius of an existing mature tree. Boring, air spade or other excavation method as approved by the City Arborist shall be considered to protect existing mature tree. Consult with the City Arborist prior to adjusting locations of utility lines. [SDR] [PUBLIC WORKS]

EP-28. DAMAGE TO EXISTING PUBLIC IMPROVEMENTS:

Developer shall be responsible to rectify any damage to the existing public improvements fronting and adjacent to the project site as a result of project construction, to City's satisfaction by the Public Works Department. All existing streetlight conduits, streetlight wires, streetlight pull boxes, traffic detector loops, and traffic signal conduits shall be protected in place during construction. Any damaged streetlight conduits, streetlight wires, streetlight pull boxes, traffic detector loops, and traffic signal conduits shall be replaced within 7 days at the expense of the developer. [COA] [PUBLIC WORKS]

EP-29. RECORD DRAWINGS:

Stamped and signed hard copy record drawings of the off-site improvements (including off-site street, sewer, water, storm drain and landscaping plans) shall be submitted to the City prior to encroachment permit sign-off. In addition, streetlight record drawings shall be in AutoCAD format & GIS format. Developer shall pay the record drawing fee. [COA] [PUBLIC WORKS]

EP-30. PUBLIC WORKS DEVELOPMENT FEES:

Developer shall pay all applicable Public Works development fees associated with the project, including but not limited to, utility frontage and/or connection fees, off-site improvement plan check and inspection fees, prior to map recordation or any permit issuance, whichever occurs first. The exact fee amount shall be determined based upon the fee rate at the time of fee payment. [COA] [PUBLIC WORKS]

EP-31. IMPROVEMENT AGREEMENT AND IMPROVEMENT SECURITIES:

Developer shall execute an Improvement Agreement and provide improvement securities and/or cash deposit(s) for all proposed public improvements prior to any permit issuance. [COA] [PUBLIC WORKS]

EP-32. OFF-SITE IMPROVEMENT COST ESTIMATE:

Provide an itemized engineer's estimate for all off-site public improvements for the entire project. [COA] [PUBLIC WORKS]

PF: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS AND/OR SHALL BE MET PRIOR TO RELEASE OF UTILITIES OR ISSUANCE OF A CERTIFICATE OF OCCUPANCY.

PF-1. COMPLETION OF PUBLIC IMPROVEMENTS:

Developer shall complete all required public improvements in accordance with City approved plans, prior to any building occupancy. [COA] [PUBLIC WORKS]

PF-2. LANDSCAPING AND IRRIGATION:

All landscaping and irrigation as contained in the approved building permit plan shall be installed prior to occupancy. [COA] [PLANNING]

PF-3. COMPACT SPACES:

All such areas shall be clearly marked prior to occupancy, as indicated on the approved building permit plans. [COA] [PLANNING]

PF-4. PARKING LOT STRIPING:

All parking lot striping, carpool and compact spaces shall be striped as per the approved plans and Public Works standards. [COA] (PLANNING/ENGINEERING)

DC: THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES DURING THE CONSTRUCTION PHASE OF THE PROJECT.

DC-1. BLUEPRINT FOR A CLEAN BAY:

The project shall be in compliance with stormwater best management practices for general construction activity until the project is completed and either final occupancy has been granted. [SDR] [PLANNING]

DC-2. TREE PROTECTION:

All tree protection shall be maintained, as indicated in the tree protection plan, until construction has been completed and the installation of landscaping has begun. [COA] [PLANNING]

DC-3. CLIMATE ACTION PLAN – OFF ROAD EQUIPMENT REQUIREMENT:

- a) Idling times will be minimized either by shutting equipment off when not in use or reducing the maximum idling time to 5 minutes (as required by the California airborne toxics control measure Title 13, Section 2485 of California Code of Regulations [CCR]), or less. Clear signage will be provided at all access points to remind construction workers of idling restrictions.
- b) Construction equipment must be maintained per manufacturer’s specifications.
- c) Planning and Building staff will work with project applicants to limit GHG emissions from construction equipment by selecting one of the following measures, at a minimum, as appropriate to the construction project:
 - i) Substitute electrified or hybrid equipment for diesel- and gasoline-powered equipment where practical.
 - ii) Use alternatively fueled construction equipment on-site, where feasible, such as compressed natural gas (CNG), liquefied natural gas (LNG), propane, or biodiesel.
 - iii) Avoid the use of on-site generators by connecting to grid electricity or utilizing solar-powered equipment.
 - iv) Limit heavy-duty equipment idling time to a period of 3 minutes or less, exceeding CARB regulation minimum requirements of 5 minutes. [COA] [PLANNING]

DC-4. DUST CONTROL:

At all times, the Bay Area Air Quality Management District’s CEQA Guidelines and “Basic Construction Mitigation Measures Recommended for All Proposed Projects”, shall be implemented. [COA] [PLANNING]

AT: THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES THAT THE USE PERMITTED BY THIS PLANNING APPLICATION OCCUPIES THE PREMISES.

AT-1. HOURS OF OPERATION:

The use permitted as part of this application shall comply with the following hours of operation at all times:

- a) The hours of operation are limited to 6:00 a.m. to midnight for standard hours of operation, excluding short duration sales events which may have extended hours. Hours extending beyond midnight shall require approval of the Director of Community Development through a Miscellaneous Plan Permit. [COA] [PLANNING]
- AT-2. DELIVERY HOURS:
Delivery hours for the approved use shall comply with SMC 19.42.030:
- a) Delivery hours are limited to daytime (period from 7:00 a.m. to 10:00 p.m. daily) only.
- b) Nighttime delivery (period from 10 p.m. to 7:00 a.m. daily) is prohibited. [SDR] [PLANNING]
- AT-3. RECYCLING AND SOLID WASTE:
All exterior recycling and solid waste shall be confined to approved receptacles and enclosures. [COA] [PLANNING]
- AT-4. LOUDSPEAKERS PROHIBITED:
Out-of-door loudspeakers shall be prohibited at all times. [COA] [PLANNING]
- AT-5. EXTERIOR EQUIPMENT:
All unenclosed materials, equipment and/or supplies of any kind shall be maintained within approved enclosure area. Any stacked or stored items shall not exceed the height of the enclosure. Individual air conditioning units shall be screened with architecture or landscaping features. [COA] [PLANNING]
- AT-6. LANDSCAPE MAINTENANCE:
All landscaping shall be installed in accordance with the approved landscape plan and shall thereafter be maintained in a neat, clean, and healthful condition. Trees shall be allowed to grow to the full genetic height and habit (trees shall not be topped). Trees shall be maintained using standard arboriculture practices. [COA] [PLANNING]
- AT-7. AWNINGS:
Fabric awnings shall be replaced at least every five (5) years. Any change of color, materials or design and are subject to review and approval by the Director of Community Development. [COA] [PLANNING]
- AT-8. PARKING LOT MAINTENANCE:
The parking lot shall be maintained in accordance with the approved plans and as follows:

- a) Clearly mark all employee, customer, and compact spaces. This shall be specified on the Building Permit plans and completed prior to occupancy.
- b) Maintain all parking lot striping and marking.
- c) Assure that adequate lighting is available in parking lots to keep them safe and desirable for the use.
- d) Require signs to direct vehicles to additional parking spaces on-site, as needed.
- e) Clearly mark all compact spaces as per approved plans. [COA]
[PLANNING]