

Mobilehome Site Standards

State of California Housing and Community Development

Title 25, CCR Section 1330/Mobilehomes

(a) In parks, or portions of parks, constructed prior to September 15, 1961, units shall not be located closer than six (6) feet from any permanent building or another unit.

(b) In parks, or portions of parks, constructed on or after September 15, 1961, minimum separation distance shall be as follows:

(1) from a unit to any permanent building, not less than ten (10) feet.

(2) from a unit to any other unit, not less than:

(A) ten (10) feet from the side of one unit to the side of an adjacent unit;

(B) eight (8) feet from the side of one unit to the front or rear of an adjacent unit; and

(C) six (6) feet from the front or rear of one unit to the front or rear of an adjacent unit.

(c) A minimum setback of three (3) feet shall be maintained from the unit or the unit's projection or eave overhang and the adjacent lot line or property line. However, a unit may be installed up to a park roadway or common area provided there is no combustible building or structure in the common area within six (6) feet, and no building or structure of any kind within three (3) feet, of any portion of the unit. The maximum seventy-five percent (75%) lot coverage allowed by section 1110 of this chapter shall be maintained. Projections or eave overhangs shall not extend beyond a lot line bordering a roadway or common area.

(d) Unit projections or eave overhangs may intrude into the minimum distances required for separation, where separation requirements between units, as defined in subsection (b) of this section, are greater than six (6) feet, provided not less than a six (6)-foot separation is maintained between the edge of any unit projection or eave overhang, and an adjacent unit, permanent building, or combustible accessory building or structure and its projection, or eave overhang.

(e) Lot lines shall be identified as prescribed by section 1104.

(f) Units installed outside of parks shall comply with local requirements for setbacks and separations and shall not be required to have greater setbacks or separation than other similar dwellings within the local agency's jurisdiction.

(g) Setback and separation requirements for accessory buildings and structures or building components are contained in section 1428 of Article 9."

Title 25, CCR Section 1428/Accessory Structures

(a) *“In parks, accessory buildings or structures, or any part thereof, on a lot shall maintain the following setbacks from lot lines:*

(1) When constructed of noncombustible materials:

(A) may be up to the lot line, provided a minimum three (3)-foot clearance is maintained from any other unit, accessory building or structure, or building component on adjacent lots.

(2) When constructed of combustible materials:

(A) a minimum three (3)-foot clearance from all lot lines, and

(B) a minimum six (6)-foot clearance from any other unit, accessory buildings or structures, or building components on adjacent lots constructed of combustible materials.

(b) Cabañas shall meet the location requirements for units, as referenced in section 1330 of this chapter.

(c) Location requirements governing private garages and storage buildings are contained in section 1443.

(d) Stairways with landings not to exceed twelve (12) square feet may be installed to the lot line provided they are located a minimum of three (3) feet from any unit, or accessory building or structure, including another stairway, on an adjacent lot. However, if the stairway is an up-and-over design (steps up the front and down the back) that provides access to the lot beyond the stairway, it does not need to maintain the separation from a unit or accessory building or structure, including another stairway, on an adjacent lot.

(e) Fencing of any material, that meets the requirements of section 1514 of this article, may be installed up to a lot line.

(f) No portion of an accessory building or structure, or building component shall project over or beyond a lot line.

(g) Any accessory building or structure, or building component may be installed up to a lot line bordering a roadway or common area provided there is no combustible building or structure in the common area within six (6) feet and no building or structure of any kind within three (3) feet of any portion of the accessory building or structure, or building component. The maximum seventy-five percent (75%) lot coverage allowed by section 1110 of this chapter shall be maintained.

(h) Wood awning or carport support posts four (4) inches or greater in nominal thickness may be located up to a lot line provided the remainder of the awning or carport is composed of noncombustible material.”