RECOMMENDED CONDITIONS OF APPROVAL AND STANDARD DEVELOPMENT REQUIREMENTS NOVEMBER 9, 2015

Planning Application 2015-7872

825 Tamarack Lane

Design Review for a new two-story single-family home of 3,026 square feet (2,626 square foot living area and 400 square foot garage) and 55% FAR. The existing 1,374 square foot one-story single-family home will be demolished. This project supersedes the previous project (2015-7266) that was denied by the Planning Commission.

The following Conditions of Approval [COA] and Standard Development Requirements [SDR] apply to the project referenced above. The COAs are specific conditions applicable to the proposed project. The SDRs are items which are codified or adopted by resolution and have been included for ease of reference, they may not be appealed or changed. The COAs and SDRs are grouped under specific headings that relate to the timing of required compliance. Additional language within a condition may further define the timing of required compliance. Applicable mitigation measures are noted with "Mitigation Measure" and placed in the applicable phase of the project.

In addition to complying with all applicable City, County, State and Federal Statutes, Codes, Ordinances, Resolutions and Regulations, Permittee expressly accepts and agrees to comply with the following Conditions of Approval and Standard Development Requirements of this Permit:

GC: THE FOLLOWING GENERAL CONDITIONS AND STANDARD DEVELOPMENT REQUIREMENTS SHALL APPLY TO THE APPROVED PROJECT.

GC-1. CONFORMANCE WITH APPROVED PLANNING APPLICATION:

All building permit drawings and subsequent construction and operation shall substantially conform with the approved planning application, including: drawings/plans, materials samples, building colors, and other items submitted as part of the approved application. Any proposed amendments to the approved plans or Conditions of Approval are subject to review and approval by the City. The Director of Community Development shall determine whether revisions are considered major or minor. Minor changes are subject to review and approval by the Director of Community Development. Major changes are subject to review at a public hearing. [COA] [PLANNING]

GC-2. PERMIT EXPIRATION:

The permit shall be null and void two years from the date of approval by the final review authority at a public hearing if the approval is not exercised, unless a written request for an extension is received prior to expiration date and is approved by the Director of Community Development. [SDR] [PLANNING]

GC-3. ENCROACHMENT PERMIT:

Prior to any work in the public right-of-way, obtain an encroachment permit with insurance requirements for all public improvements including a traffic control plan per the latest California Manual on Uniform Traffic Control Devices (MUTCD) standards to be reviewed and approved by the Department of Public Works. [COA] [PUBLIC WORKS] (SMC 13.08.030, SMC 13.08.60 and SMC 13.08.070)

GC-4. FIRE SPRINKLER SYSTEM:

An approved automatic fire sprinkler system designed and installed in accordance with NFPA 13D is required throughout the house.

PS: THE FOLLOWING CONDITIONS SHALL BE MET PRIOR TO SUBMITTAL OF BUILDING PERMIT, AND/OR GRADING PERMIT.

PS-1. EXTERIOR MATERIALS REVIEW:

Final exterior building materials and color scheme are subject to review and approval by the Director of Community Development prior to submittal of a building permit. [COA] [PLANNING]

BP: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS SUBMITTED FOR ANY DEMOLITION PERMIT, BUILDING PERMIT, GRADING PERMIT, AND/OR ENCROACHMENT PERMIT AND SHALL BE MET PRIOR TO THE ISSUANCE OF SAID PERMIT(S).

BP-1. CONDITIONS OF APPROVAL:

Final plans shall include all Conditions of Approval included as part of the approved application starting on sheet 2 of the plans. [COA] [PLANNING]

BP-2. RESPONSE TO CONDITIONS OF APPROVAL:

A written response indicating how each condition has or will be addressed shall accompany the building permit set of plans. [COA] [PLANNING]

BP-3. BLUEPRINT FOR A CLEAN BAY:

The building permit plans shall include a "Blueprint for a Clean Bay" on one full sized sheet of the plans. [SDR] [PLANNING]

BP-4. GREEN BUILDING:

The plans submitted for building permits shall demonstrate compliance with the CALGreen Mandatory Measures and achieve a minimum of 80 points on the Green Point Rated checklist. Project plans shall be accompanied with a letter from the project's Green Point Rater/LEED AP verifying the project is designed to achieve the required points. [COA] [PLANNING/BUILDING]

BP-5. LANDSCAPE PLAN:

If the new or modified landscaping area cumulatively exceeds 2,500 square feet, landscape and irrigation plans shall be prepared by a certified professional, and shall comply with Sunnyvale Municipal Code Chapter 19.37 requirements. New or modified landscaping area that cumulatively exceeds 1,000 square feet shall also comply with Sunnyvale Municipal Code Chapter 19.37 requirements. If the project is subject to the requirements of Chapter 19.37, landscape and irrigation plans are subject to review and approval by the Director of Community Development through the submittal of a Miscellaneous Plan Permit (MPP). [COA] [PLANNING]

BP-6. TREE PROTECTION PLAN:

Prior to issuance of a Demolition Permit, a Grading Permit or a Building Permit, whichever occurs first, obtain approval of a tree protection plan from the Director of Community Development. Two copies are required to be submitted for review.

- a) Provide fencing around the drip line of the trees that are to be saved and ensure that no construction debris or equipment is stored within the fenced area during the course of demolition and construction.
- b) The tree protection plan shall be installed prior to issuance of any Building or Grading Permits, subject to the on-site inspection and approval by the City Arborist and shall be maintained in place during the duration of construction and shall be added to any subsequent building permit plans. [COA] [PLANNING/CITY ARBORIST]

BP-7. BEST MANAGEMENT PRACTICES:

The project shall comply with the following source control measures as outlined in the BMP Guidance Manual and SMC 12.60.220. Best management practices shall be identified on the building permit set of plans and shall be subject to review and approval by the Director of Public Works:

a) Storm drain stenciling. The stencil is available from the City's Environmental Division Public Outreach Program, which may be reached by calling (408) 730-7738.

- b) Landscaping that minimizes irrigation and runoff, promotes surface infiltration where possible, minimizes the use of pesticides and fertilizers, and incorporates appropriate sustainable landscaping practices and programs such as Bay-Friendly Landscaping.
- c) Appropriate covers, drains, and storage precautions for outdoor material storage areas, loading docks, repair/maintenance bays, and fueling areas.
- d) Covered trash, food waste, and compactor enclosures.
- e) Plumbing of the following discharges to the sanitary sewer, subject to the local sanitary sewer agency's authority and standards:
 - i) Discharges from indoor floor mat/equipment/hood filter wash racks or covered outdoor wash racks for restaurants.
 - ii) Dumpster drips from covered trash and food compactor enclosures.
 - iii) Discharges from outdoor covered wash areas for vehicles, equipment, and accessories.
 - iv) Swimming pool water, spa/hot tub, water feature and fountain discharges if discharge to onsite vegetated areas is not a feasible option.
 - v) Fire sprinkler test water, if discharge to onsite vegetated areas is not a feasible option. [SDR] [PLANNING]

BP-8. CONSTRUCTION MATERIAL AND STAGING:

All construction related materials, equipment, and construction workers parking need to be managed on-site and not located in the public right-of-ways or public easements. [SDR] [PUBLIC WORKS]

PF: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS AND/OR SHALL BE MET PRIOR TO RELEASE OF UTILITIES OR ISSUANCE OF A CERTIFICATE OF OCCUPANCY.

PF-1. LANDSCAPING AND IRRIGATION:

All landscaping and irrigation as contained in the approved building permit plan shall be installed prior to occupancy. [COA] [PLANNING]

DC: THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES DURING THE CONSTRUCTION PHASE OF THE PROJECT.

DC-1. BLUEPRINT FOR A CLEAN BAY:

The project shall be in compliance with stormwater best management practices for general construction activity until the project is completed and either final occupancy has been granted. [SDR] [PLANNING]

DC-2. TREE PROTECTION:

All tree protection shall be maintained, as indicated in the tree protection plan, until construction has been completed and the installation of landscaping has begun. [COA] [PLANNING]

DC-3. CLIMATE ACTION PLAN – OFF ROAD EQUIPMENT REQUIREMENT:

- OR 2.1: Idling times will be minimized either by shutting equipment off when not in use or reducing the maximum idling time to 5 minutes (as required by the California airborne toxics control measure Title 13, Section 2485 of California Code of Regulations [CCR]), or less. Clear signage will be provided at all access points to remind construction workers of idling restrictions.
- OR 2.2: Construction equipment must be maintained per manufacturer's specifications.
- OR 2.3: Planning and Building staff will work with project applicants to limit GHG emissions from construction equipment by selecting one of the following measures, at a minimum, as appropriate to the construction project:
 - a) Substitute electrified or hybrid equipment for diesel- and gasoline-powered equipment where practical.
 - b) Use alternatively fueled construction equipment on-site, where feasible, such as compressed natural gas (CNG), liquefied natural gas (LNG), propane, or biodiesel.
 - c) Avoid the use of on-site generators by connecting to grid electricity or utilizing solar-powered equipment.
 - d) Limit heavy-duty equipment idling time to a period of 3 minutes or less, exceeding CARB regulation minimum requirements of 5 minutes. [COA] [PLANNING]

DC-4. DUST CONTROL:

At all times, the Bay Area Air Quality Management District's CEQA Guidelines and "Basic Construction Mitigation Measures Recommended for All Proposed Projects", shall be implemented. [COA] [PLANNING]

AT: THE FOLLOWING CONDITIONS SHALL BE COMPLIED WITH AT ALL TIMES THAT THE USE PERMITTED BY THIS PLANNING APPLICATION OCCUPIES THE PREMISES.

AT-1. SECOND FLOOR WINDOWS:

The second floor windows identified on the approved plans as having obscured glass or window sill heights at least five feet above the finished floor shall continue to remain in effect. Any proposed modifications shall be reviewed by the Director of Community Development. [COA] [PLANNING]