RECOMMENDED CONDITIONS OF APPROVAL AND STANDARD DEVELOPMENT REQUIREMENTS

Planning Application 2017-7071

495 Java Drive

PARCEL MAP to subdivide one lot into two lots (common area between office buildings) for NetApp and Google.

The following Conditions of Approval [COA] and Standard Development Requirements [SDR] apply to the project referenced above. The COAs are specific conditions applicable to the proposed project. The SDRs are items which are codified or adopted by resolution and have been included for ease of reference, they may not be appealed or changed. The COAs and SDRs are grouped under specific headings that relate to the timing of required compliance. Additional language within a condition may further define the timing of required compliance. Applicable mitigation measures are noted with "Mitigation Measure" and placed in the applicable phase of the project. The Mitigation Monitoring and Reporting Program is included Exhibit 1 and reference Site Plan is included in Exhibit 2.

In addition to complying with all applicable City, County, State and Federal Statutes, Codes, Ordinances, Resolutions and Regulations, Permittee expressly accepts and agrees to comply with the following Conditions of Approval and Standard Development Requirements of this Permit:

GC: THE FOLLOWING GENERAL CONDITIONS AND STANDARD DEVELOPMENT REQUIREMENTS SHALL APPLY TO THE APPROVED PROJECT.

GC-1. CONFORMANCE WITH APPROVED PLANNING APPLICATION:

All building permit drawings and subsequent construction and operation shall substantially conform with the approved planning application, including: drawings/plans, materials samples, building colors, and other items submitted as part of the approved application. Any proposed amendments to the approved plans or Conditions of Approval are subject to review and approval by the City. The Director of Community Development shall determine whether revisions are considered major or minor. Minor changes are subject to review and approval by the Director of Community Development. Major changes are subject to review at a public hearing. [COA] [PLANNING]

GC-2. RECORDATION OF PARCEL MAP:

This project is subject to, and contingent upon recordation of a parcel map. The submittal, approval and recordation of the parcel map shall be in accordance with the provisions of the California Subdivision Map Act and Sunnyvale Municipal Code Title 18 Subdivision requirements. Parcel map shall be recorded prior to any grading or building permit issuance of any building located on that certain lot as shown on the corresponding parcel map. [COA] [PUBLIC WORKS]

GC-3. SIDEWALK IMPROVEMENTS:

Prior to the parcel map recordation, the developer shall install a 6-foot sidewalk along Geneva Drive frontage where there is no existing sidewalk (approximately 215-feet in length). Provide sidewalk transition to conform to existing sidewalk at south and north ends of the project limits. This sidewalk connection may require the dedication of a sidewalk easement to accommodate a meandering sidewalk in order to save existing street trees, as determined by the Department of Public Works. The sidewalk easement shall be by separate instrument and shall be recorded prior to issuance of encroachment permit [COA] [PUBLIC WORKS]

GC-4 PARKING LOT IMPROVEMENTS

Prior to approval of the Final Map, a Miscellaneous Plan Permit shall be submitted for review and approval for a parking lot design located on Site 2 (Google). The parking lot shall be designed to meet all design standards (S.M.C. 19.46.120) for landscaping, shading, stormwater runoff, etc. The parking area shall only be constructed if the demand is warranted based on occupancy of the buildings (described as Buildings #1, #3, #4 on plan page A1) on-site. [COA] [PLANNING]

GC-5. PUBLIC IMPROVEMENTS:

Developer shall install public improvements as required by Sunnyvale Municipal Code Sections 18.08, including but not limited to, curb & gutter, sidewalks, driveway approaches, street pavements, utility extensions and connections, meters/vaults, trees and landscaping, traffic signs, etc.

All public improvements shall be designed and constructed in accordance with current City design standards, standard details and specifications, and Americans with Disabilities Act (ADA) requirements where applicable, unless otherwise approved by the Department of Public Works. The site development plan is subject to change during the plan check process.

The developer is required to complete the installation of all public improvements and other improvements deemed necessary by the Public Works Department, prior to occupancy of the first building, or to the satisfaction of the Public Works Department. [COA] [PUBLIC WORKS]

GC-6. OFF-SITE IMPROVEMENT PLANS:

Submit off-site improvement plans separate from the building on-site improvement plans as the off-site improvement plans are approved through a public works encroachment permit process. [SDR] [PUBLIC WORKS]

GC-7. ENCROACHMENT PERMIT:

Prior to any work in the public right-of-way or easement area, obtain an encroachment permit with insurance requirements for all public improvements including a traffic control plan per the latest California Manual on Uniform Traffic Control Devices (MUTCD) standards to be reviewed and approved by the Department of Public Works. [COA] [PUBLIC WORKS]

GC-8. EASEMENT DEDICATION:

This project requires a 15-foot public utility easement located between Parcel 6 and Parcel 12, as determined by the Department of Public Works, to accommodate the existing 36-inch storm drain being relocated out of the Parcel 12 lot. The public utility easement shall be by separate instrument and shall be recorded prior to any grading or building permit issuance of any building located on Parcel 12 lot as shown on the corresponding parcel map. [COA] [PUBLIC WORKS]

GC-9. FIRE ACCESS, PARKING LOT & PRIVATE UTILITY MODIFICATIONS: The developer shall demonstrate through supporting exhibits how fire/private access and private utilities (i.e. existing domestic/fire water, irrigation, sanitary sewer, storm drain, etc.) are independently maintained and completely separated on each proposed common lot. Necessary onsite modifications to separate the two proposed common lots from shared fire/private access (not identified in the tentative parcel map), private utilities (including irrigation), treatment facilities, cross-lot drainage, etc. shall be mitigated prior to parcel map recordation. [COA] [PUBLIC WORKS]

GC-10. CONDITIONS OF APPROVAL:

All Public Works Conditions of Approval (COA) associated with Planning Application 2011-7759 apply to this tentative map application. [COA] [PUBLIC WORKS]

PS: THE FOLLOWING CONDITIONS SHALL BE MET PRIOR TO SUBMITTAL OF ENCROACHMENT PERMIT, BUILDING PERMIT AND/OR GRADING PERMIT.

Prior to first off-site plan check submittal, submit a focused sanitary sewer analysis, to be reviewed and approved by the City, identifying the overall project impact to the City's existing sanitary sewer main(s). This includes, but is not limited to, the following:

- a) A detailed estimate of water consumption in gallons per day or estimate of sanitary sewer discharge in gallons per day; and
- b) Any incremental impact that will result from the new project in comparison to the existing sewer capacity of the immediate downstream mainline as needed, and allocation of wastewater discharge from the project site to each of the proposed laterals. Any deficiencies in the existing system in the immediate vicinity of the project will need to be addressed and resolved at the expense of the developer as part of the off-site improvement plans. Sewer flow data may be required as needed. Any mitigation improvements needed shall be incorporated into the first plan check submittal. [COA] [PUBLIC WORKS]

BP: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS SUBMITTED FOR ANY DEMOLITION PERMIT, BUILDING PERMIT, GRADING PERMIT, AND SHALL BE MET PRIOR TO THE ISSUANCE OF SAID PERMIT(S).

BP-1. DEMOLITION/CONSTRUCTION/RECYCLING WASTE REPORT FORM: To mitigate the impacts of large projects on local waste disposal and recycling levels, demolition waste weights/volumes, construction weights/volumes, and recycling weights/volumes are to be reported to the City, per City's "waste & recycling reporting form" (electronic copy available) or a similar chart approved by the City. As part of the project's construction specifications, the developer shall track the type, quantity, and disposition of materials generated, and forward a complete report to the Department of Environmental Services, Solid Waste Division both periodically and at project completion [COA][ENVIRONMENTAL SERVICES]

BP-2. SOLID WASTE AND RECYCLING ENCLOSURE:

The building permit plans shall include details for the installation of recycling and solid waste enclosures that are consistent with SMC 19.38.030. The solid waste disposal and recycling facilities within the enclosure area or within buildings shall be designed with adequate size, space and clearance based upon City's latest guidelines. The required enclosures shall:

- a) Match the design, materials and color of the main building;
- b) Be of masonry construction;
- c) Be screened from view;
- d) All gates, lids and doors shall be closed at all times;
- e) Shall not conflict with delivery/receiving areas;

- f) Shall be consistent with the approved Solid Waste and Recycling Management Plan;
- g) Solid waste and recycling diversion systems shall be incorporated into the facilities and tenant improvements. [COA] [PLANNING/ENVIRONMENTAL SERVICES]
- BP-3. SOLID WASTE DISPOSAL AND RECYCLING DESIGN PLAN:

A detailed solid waste disposal and recycling design plan shall be submitted for review and approval by the Director of Community Development prior to issuance of building permit. The solid waste disposal plan and building permit plans shall demonstrate compliance with current City requirements and guidelines for non-residential projects. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

- BP-4. STORMWATER MANAGEMENT PLAN:
 Submit two copies of a Stormwater Management Plan subject to review and approval by Director of Community Development, pursuant to SMC 12.60, prior to issuance of building permit. The Stormwater
 - 12.60, prior to issuance of building permit. The Stormwater Management Plan shall include an updated Stormwater Management Data Form. [COA] [PLANNING/ENVIRONMENTAL SERVICES]
- BP-5. STORMWATER MANAGEMENT PLAN THIRD-PARTY CERTIFICATION: Third-party certification of the Stormwater Management Plan is required per the following guidance: City of Sunnyvale Stormwater Quality BMP Applicant Guidance Manual for New and Redevelopment Projects Addendum: Section 3.1.2 Certification of Design Criteria Third-Party Certification of Stormwater Management Plan Requirements. The third-party certification shall be provided prior to building permit issuance. [SDR] [PLANNING/ENVIRONMENTAL SERVICES]
- BP-6. CONSTRUCTION MATERIAL AND STAGING:
 All construction related materials, equipment, and construction workers parking need to be managed on-site and not located in any public right-of-ways or public easements. [COA] [PUBLIC WORKS]
- BP-7. PARCEL MAP:

This project is subject to, and contingent upon recordation of a parcel map to create a new property line splitting the existing Common Lot. The submittal, approval and recordation of the parcel map shall be in accordance with the provisions of the California Subdivision Map Act and Sunnyvale Municipal Code Title 18 Subdivision requirements. Parcel map shall be recorded prior to any grading or building permit issuance of any building located on that certain lot as shown on the corresponding parcel map. [COA] [PUBLIC WORKS]

BP-8. EASEMENT VACATION:

Prior to any building permit issuance for Parcel 12 lot, the existing 10-foot Public Utility Easement running through the Parcel 12 lot shall be vacated by separate instrument and a recorded/conformed copy provided to the City. [COA] [PUBLIC WORKS]

EP: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED AS PART OF AN ENCROACHMENT PERMIT APPLICATION.

EP-1. MOFFETT PARK SPECIFIC PLAN:

This project is in the Moffett Park Specific Plan (MPSP) area, therefore, the developer shall comply with any applicable design requirements as identified in the MPSP or as amended and approved by the City. [COA] [PUBLIC WORKS]

EP-2. COMPLETE OFF-SITE IMPROVEMENT PLAN SET:

A complete plan check set applicable to the project, which may include street improvement plans, streetscape plans, erosion control plans, and traffic control plans shall be submitted as part of the first off-site improvement plans, including off-site engineering cost estimate. Joint trench plans (if applicable) may be submitted at a later date. No partial sets are allowed unless otherwise approved by the Department of Public Works. See Improvement Plan Checklist and Improvement Plan Submittal Checklist at the following 2 links:

https://sunnyvale.ca.gov/civicax/filebank/blobdload.aspx?BlobID=2 4002

https://sunnyvale.ca.gov/civicax/filebank/blobdload.aspx?BlobID=23625 [COA] [PUBLIC WORKS]

EP-3. BENCHMARKS:

The improvement plans shall be prepared by using City's latest benchmarks (NAVD88) available on City's website https://sunnyvale.ca.gov/civicax/filebank/blobdload.aspx?BlobID=2 3803 Plans based on NGVD29 will not be accepted. [COA] [PUBLIC WORKS]

EP-4. UPGRADE OF EXISTING IMPROVEMENTS:

As part of the off-site improvement plan review and approval, any existing public improvements to be re-used by the project, which are not in accordance with current City standards and are not specifically identified in the herein project conditions shall be upgraded to current City standards and as required by the Department of Public Works. [COA] [PUBLIC WORKS]

EP-5. UTILITY CONNECTION:

This project requires connection to all City utilities or private utilities operating under a City or State franchise which provide adequate levels of service. [COA] [PUBLIC WORKS]

EP-6. UTILITY CONNECTION TO THE MAIN:

All sanitary sewer laterals connecting to the existing main line shall be at a new sanitary sewer manhole, or as determined by Public Works. All storm drain laterals connecting to the main shall be at a new storm drain manhole, except where a pipe to pipe connection is permitted if the mainline is 36" or larger, or a junction structure is permitted where the point of connection is within close vicinity of an existing downstream manhole. Pursuant to City design standards, any new and retrofitted sanitary sewer manholes require Sewpercoat, Mainstay or Sancon calcium aluminate cementitious mortar coating of the interior. [SDR] [PUBLIC WORKS]

EP-7. POTHOLING OF EXISTING DRY UTILITIES:

Concurrent with the initial submittal of off-site improvement plans, obtain an encroachment permit for potholing purposes to locate existing dry utilities. Use pothole information to identify possible conflict between the proposed location of City trees and existing utilities, proposed joint trench, and proposed connection of gravity utilities. Potholing is to take place in a timely manner so that this does not hold up the review of the improvement plans. [COA] [PUBLIC WORKS]

EP-8. EXISTING UTILITY ABANDONMENT:

Developer is responsible for research on all existing utility lines to ensure that there are no conflicts with the project. All existing utility lines (public or private) and/or their appurtenances not serving the project and/or have conflicts with the project, shall be capped, abandoned, removed, relocated and/or disposed of to the satisfaction of the City. Existing public facilities within the street right-of-way shall be abandoned per City's Abandonment Notes and procedures, including abandonment by other utility owners. [COA] [PUBLIC WORKS]

EP-9. MODIFICATIONS TO EXISTING PUBLIC UTILITIES:

Developer is required to pay for all changes or modifications to existing city utilities, streets and other public utilities within or adjacent to the project site, including but not limited to utility facilities/conduits/vaults relocation due to grade change in the sidewalk area, caused by the development. [COA] [PUBLIC WORKS]

EP-10. DRY UTILITIES:

Submit dry utility plans and/or joint trench plans (PG&E, telephone, cable TV, fiber optic, etc.) to the Public Works Department for review

and approval prior to issuance of any permits for utility work within any public right-of-way or public utility easements. Separate encroachment permits shall be required for various dry utility construction. [SDR] [PUBLIC WORKS]

EP-11. WET UTILITIES:

All wet utilities (water, sanitary sewer, storm drain) on private property shall be privately owned and maintained. The fire and domestic water systems shall be privately owned and maintained beyond the meter. [COA] [PUBLIC WORKS]

EP-12. RE-USE OF EXISTING CITY UTILITY SERVICE LINES:

The re-use of existing City water service lines is not allowed. Re-use of existing City sanitary sewer and storm drain service lines and appurtenances is subject to City's review and approval. Developer's contractor shall expose the existing facilities during construction for City's evaluation or provide video footage of the existing pipe condition. Developer's contractor shall replace any deficient facilities as deemed necessary by Public Works Department. [COA] [PUBLIC WORKS]

EP-13: SEPARATE AND INDEPENDENT UTILITY SERVICE LINES: Each building shall have separate and independent utility service lines tapped to the main. [COA] [PUBLIC WORKS]

EP-14. SEPARATE DOMESTIC/FIRE PROTECTION SERVICE LINE:

Provide separate fire and domestic service lines to each building. Provide separate fire service tap(s) to the street main for on-site fire hydrants. Install reduced pressure detector assembly (RPDA) behind the street right-of-way. [COA] [PUBLIC WORKS/PUBLIC SAFETY-FIRE PREVENTION]

EP-15. WATER METER:

Each building shall have its own domestic water service connection to the water main with domestic radio-read water meter and reduced pressure backflow prevention devices per current City standards. For water meter sizes three (3) inches or larger, provide meter sizing calculations to Public Works Department for approval of meter size, as part of the off-site improvement plan submittal. If the buildings water demand requires a water meter 3" or larger, installation of dual meters and a cut-in tee are required per City standard detail 12B and 12B-1. Provide separate fire service taps with separate reduced pressure detector assembly in accordance with current City standards. Install new radio-read water meter(s) for each point of connection to the water main. Install new backflow prevention devices on the discharge side of water service line on private property. Install backflow preventer enclosure where applicable. [SDR] [PUBLIC WORKS]

EP-16. IRRIGATION SERVICE LINE AND BACKFLOW PREVENTORS:

This project requires connection to city's existing reclaimed water system for irrigation purpose. Install a separate irrigation water service line (separate from the domestic water service line) with a meter and backflow prevention device.

All landscape and irrigation systems, located in the public park strip areas shall be connected to the water system metered to the property owner. Install new reduced pressure backflow prevention devices on the discharge side of irrigation line on private property. Install backflow preventer enclosure where applicable. Backflows must adhere to City's Cross-Connection Program. Backflow inspection permit and tags are required for all backflow devices.

Developer shall follow and implement the requirements for reclaimed water usage/identification to comply with California Department of Environmental Health: Title 22 - Division 4 of the Administrative Code.

EP-17. RECLAIMED WATER:

The use of reclaimed water requires a Recycled Water Permit from the City. Contact Environmental Services Department/Water Operations at 408-730-2744 for further information. [SDR] [PUBLIC WORKS]

EP-18. SANITARY SEWER AND STORMDRAIN MANHOLES:

Install new sanitary sewer and storm drain manholes at the street rightof-way lines for all existing and proposed sanitary sewer laterals to be used for the project. [SDR] [PUBLIC WORKS]

EP-19. SANITARY SEWER VIDEO:

The contractor shall make a video copy of the interior of the new sanitary sewer mainline installed prior to it is put into service. [COA] [PUBLIC WORKS]

EP-20. SANITARY SEWER AND STORM DRAIN TRIBUTARY PATTERN:

This project is required to follow the existing sanitary sewer and storm drain tributary pattern. Any deviations would require additional analysis and be subject to approval by the Department of Public Works as part of the off-site improvement plan review process. This project shall not cause any negative impact on the drainage pattern for adjacent properties. [COA] [PUBLIC WORKS]

EP-21. STORM DRAIN DESIGN

Provide storm drain hydrology and hydraulic calculations based upon a 10-year storm event to justify the size of the storm drain lateral flowing full. The project impact to the existing storm drain main shall retain 1' below the lowest public street gutter flow elevation. EP-22. CATCH BASIN TRASH CAPTURE DEVICES AND BADGE/STENCILING: Pursuant to SMC 12.60.130, install full trash capture devices on each of the project site, prior to connecting to the City's storm drain collection system. The developer shall be responsible for perpetual maintenance of those trash capture devices. All storm drain inlet facilities located in the public right-of-way shall be stenciled and/or have a badge that read "NO DUMPING" as supplied by the Environmental Services Department. [COA] [PLANNING/ENVIRONMENTAL SERVICES]

EP-23. UTILITY METER/VAULT:

No existing or new utility meters or vaults shall be located within the new driveway approach areas. All existing or new utility vaults serving the project site shall be located on-site and not within the public utility easement, if any. [COA] [PUBLIC WORKS]

EP-24. DRIVEWAY APPROACHES:

Remove existing driveway approaches and install new driveway approaches (City Standard Detail 6C-1) along the Geneva Drive project frontage where new sidewalk is installed to comply with Americans with Disabilities Act (ADA) requirements and per city standard details and specifications. No curb-return style driveways allowed. All unused existing driveway approaches shall be replaced with new curb, gutter and sidewalk. [COA] [PUBLIC WORKS]

EP-25. STREETSCAPE IMPROVEMENTS:

Remove existing curb and gutter and install new 2-foot wide gutter, 6-inch curb, and 6-foot attached sidewalk (measured from back of curb) along the Geneva Drive frontage. Provide sidewalk transition to conform to existing sidewalk at south and north ends of the project limits. [COA] [PUBLIC WORKS]

EP-26. STREET PAVEMENT:

Apply Type II slurry seal, from lip of gutter to the centerline on Geneva Drive, fronting the area of improvements, or as directed by the Department of Public Works. [SDR] [PUBLIC WORKS]

EP-27. TRAFFIC CONTROL PLAN:

Submit a traffic control plan with the off-site improvement plans for review and approval. Per the City's Temporary Traffic Control Checklist, the traffic control plan shall include a summary of the traffic control types, dates, times and blocks affected. All construction related materials, equipment, and construction workers parking need to be stored on-site and the public streets need to be kept free and clear of construction debris. [COA] [PUBLIC WORKS]

EP-28. CITY STREET TREES:

The developer shall install required street trees along the project frontage on Geneva Drive (tree species to be provided to the developer at a later date). Street trees and frontage landscaping shall be included in the detailed landscape and irrigation plan subject to review and approval by the Department of Public Works prior to issuance of encroachment permit. New street trees shall be 24-inch box size or 15 gallon size. The city tree spacing should be approximately 35 feet apart. A continuous root barrier shall be installed along the back of sidewalk area. No trees are to be planted within 10' of a sanitary sewer lateral. [SDR] [PUBLIC WORKS]

EP-29. PROTECTION OF EXISTING TREES:

No utility trench shall be allowed within 15' radius of an existing mature tree. Boring, air spade or other excavation method as approved by the City Arborist shall be considered to protect existing mature tree. Consult with the City Arborist prior to adjusting locations of utility lines. [SDR] [PUBLIC WORKS]

EP-30. DAMAGE TO EXISTING PUBLIC IMPROVEMENTS:

Developer shall be responsible to rectify any damage to the existing public improvements fronting and adjacent to the project site as a result of project construction to City's satisfaction by the Department of Public Works. [COA] [PUBLIC WORKS]

EP-31. RECORD DRAWINGS:

Stamped and signed hard copy record drawings of the off-site improvements (including off-site street, sewer, water, storm drain and landscaping plans) shall be submitted to the City prior to encroachment permit sign-off. In addition, streetlight record drawings shall be in AutoCAD format. Developer shall pay the record drawing fee. [COA] [PUBLIC WORKS]

EP-32. STREETLIGHTS:

The developer shall upgrade all existing streetlight fixtures along Geneva Drive project frontage to LED fixtures. All LED fixtures shall be of the same make and model (current approved manufacturers are GE and Philips). [COA] [PUBLIC WORKS]

PM: THE FOLLOWING CONDITIONS SHALL BE MET PRIOR TO THE APPROVAL OF THE FINAL MAP OR PARCEL MAP.

PM-1. TITLE 18 AND SUBDIVISION MAP ACT:

The submittal, approval and recordation of the parcel map shall be in accordance with the provisions of the California Subdivision Map Act and Sunnyvale Municipal Code Title 18 subdivision requirements. [COA] [PUBLIC WORKS]

PM-2. RESERVATION/ABANDONMENT OF EASEMENTS:

Reservation of new and/or abandonment of existing public/private utility easement(s), ingress/egress easement(s) necessary for the project site shall be delineated on the map or recorded concurrently with the map with a separate instrument, unless otherwise approved by the Department of Public Works. Quitclaim deed is required for abandonment of private easements prior to map recordation. All easements shall be kept open and free from buildings and structures of any kind except those appurtenances associated with the defined easements. [COA] [PUBLIC WORKS]

PM-3. UTILITY COMPANY APPROVAL:

Obtain approval letters from various utility companies for the parcel map in regards to any existing or new easements associated with the project. [COA] [PUBLIC WORKS]

PM-4. EMERGENCY VEHICLE ACCESS EASEMENT:

Developer shall dedicate a minimum 26'-wide emergency vehicle ingress-egress easement over the surface parking areas, excepting areas for parking stalls. [COA][PUBLIC SAFETY/PUBLIC WORKS]

PM-5. PUBLIC WORKS DEVELOPMENT FEES:

Developer shall pay all applicable Public Works development fees associated with the project, including but not limited to, utility frontage and/or connection fees, off-site improvement plan check and inspection fees, prior to map recordation or any permit issuance, whichever occurs first. The exact fee amount shall be determined based upon the fee rate at the time of fee payment. [COA] [PUBLIC WORKS]

PM-6. OFF-SITE IMPROVEMENT COST ESTIMATE:

Provide an itemized engineer's estimate for all off-site public improvements for the entire project. [COA] [PUBLIC WORKS]

PF: THE FOLLOWING CONDITIONS SHALL BE ADDRESSED ON THE CONSTRUCTION PLANS AND/OR SHALL BE MET PRIOR TO RELEASE OF UTILITIES OR ISSUANCE OF A CERTIFICATE OF OCCUPANCY.

PF-1. NEW PUBLIC EASEMENTS LOCATED ON-SITE:

Any new easements required for public use purpose shall be either shown on the recorded parcel map or on a separate recorded Easement Deed deemed necessary by the Department of Public Works prior to any building occupancy. [COA] [PUBLIC WORKS]

PF-2. PARKING LOT STRIPING:

ATTACHMENT 2 2017-7071 – 495 Java Drive Page 13 of 13

All parking lot striping, guest spaces, and compact spaces shall be striped as per the approved building permit plans and Public Works standards prior to occupancy. [COA] [PLANNING/PUBLIC WORKS]

PF-3. COMPLETION OF PUBLIC IMPROVEMENTS:

Developer shall complete all required public improvements in accordance with City approved plans, prior to any building occupancy. [COA] [PUBLIC WORKS]